

Guide rollers FR
Product range

TEMCO

Guide Rollers FR


Types, sizes, surfaces




Smooth running

Guide Rollers FR Series

Product figures and overview



Mounting type 1




Mounting type 2

Type	Max. yarn speed [m/min]	Max. yarn temp. [°C]	Max. radial load [N]	Mounting type	Dimensions [mm]								Mounting specification d × l ₁ [mm]	Surface	Groove (distance)
					D (Ø)	D ₁	d	L	L ₁	l ₁	l				
FR1108-00	800	70	45	1	11	15	M3	8	23	9	–	M3 × 9	chrom	1	
FR1507-01	1000	70	55	2	15.2	18.5	–	7	1	–	5	Ø5 × 1	steel	1	
FR2016-02 ¹	630	70	14	1	20	24	Ø11	16	31	16	–	Ø11 × 16	HC	4 (3)	
FR2330 ¹	600	70	120	1	23	41	M8	30	55.85	16	–	M8 × 16	ceramic	1	
FR2330-01 ¹	600	70	120	1	23	41	M5	30	61.7	25	–	M5 × 25	ceramic	1	
FR3530-02	4 400	70	45	1	35	55	Ø8	30	70.5	25	–	Ø8 × 25	ceramic	2 (8)	
FR4018-01	5 000	70	45	1	40	59	Ø8	18	70.5	25	–	Ø8 × 25	ceramic	1	
FR4076-00	3 000	100	100	1	40	54	Ø12.5	76	103	25.5	–	Ø12.5 × 25.5	stainless steel	2 (21)	

¹ Acceptance only with minimum quantity

Guide Rollers FR26

Product figures and overview



Type	Max. yarn speed [m/min]	Max. yarn temp. [°C]	Max. radial load [N]	Dimensions [mm]												Bearing	Surface	Groove (distance)
				D (Ø)	D ₁	D ₂	D ₃	d	L	L ₁	L ₂	l	l ₁	X ²				
FR2606-01	700	70	20	26	30	31.5	31.5	5	6	2	2	4	0	5	easy-running	anodized black	1	
FR2606-02 ¹	700	70	20	26	30	31.5	31.5	5	6	2	2	4	0	5	easy-running	anodized blue	1	
FR2606-03 ¹	700	70	20	26	30	31.5	31.5	5	6	2	2	4	0	5	easy-running	anodized gray	1	
FR2606-04 ¹	700	70	20	26	30	31.5	31.5	5	6	2	2	4	0	5	easy-running	anodized red	1	
FR2606-05 ¹	700	70	20	26	30	31.5	31.5	5	6	2	2	4	0	5	easy-running	anodized green	1	
FR2607-00 ¹	700	70	20	26	32.5	31.5	31.5	5	7	–	2	5	1	3	easy-running	PC 915S	2	
FR2607-01 ¹	700	70	20	26	32.5	31.5	31.5	5	7	–	3.5	5	1	–	easy-running	PC 915S	1	
FR2608-01	700	70	60	26	35	36.5	39	5	8	2	3	5	0.5	7	standard	anodized black	1	
FR2608-02	700	70	60	26	35	36.5	39	5	8	2	3	5	0.5	7	standard	anodized blue	1	
FR2608-03	700	70	60	26	35	36.5	39	5	8	2	3	5	0.5	7	standard	anodized gray	1	
FR2608-04	700	70	60	26	35	36.5	39	5	8	2	3	5	0.5	7	standard	anodized red	1	
FR2608-05 ¹	700	70	20	26	35	36.5	39	5	8	2	3	5	0.5	7	easy-running	hardcoat	1	
FR2610-00	700	70	60	26	35	36.5	39	5	10	2	4	5	1.5	9	standard	hardcoat	1	
FR2610-01 ¹	700	70	60	26	35	36.5	39	5	10	2	4	5	1.5	9	standard	PC 915S	1	
FR2610-02	700	70	20	26	35	36.5	39	5	10	2	4	5	1.5	9	easy-running	hardcoat	1	
FR2610-04 ¹	700	70	20	26	35	36.5	39	5	10	2	4	5	1.5	9	easy-running	hard anodized black	1	
FR2610-05 ¹	700	70	20	26	35	36.5	39	5	10	2	4	5	1.5	9	easy-running	hard anodized blue	1	
FR2610-06 ¹	700	70	20	26	35	36.5	39	5	10	2	4	5	1.5	9	easy-running	hard anodized gray	1	
FR2610-07 ¹	700	70	20	26	35	36.5	39	5	10	2	4	5	1.5	9	easy-running	hard anodized red	1	
FR2610-08 ¹	700	70	20	26	35	36.5	39	5	10	2	4	5	1.5	9	easy-running	hard anodized green	1	
FR2614-01	700	70	60	26	35	36.5	39	5	14	8	3	5	0.5	12.8	standard	anodized black	1	
FR2614-02 ¹	700	70	60	26	35	36.5	39	5	14	8	3	5	0.5	12.8	standard	anodized blue	1	
FR2614-03 ¹	700	70	60	26	35	36.5	39	5	14	8	3	5	0.5	12.8	standard	anodized gray	1	
FR2614-04 ¹	700	70	60	26	35	36.5	39	5	14	8	3	5	0.5	12.8	standard	anodized red	1	
FR2614-05	700	70	20	26	35	36.5	39	5	14	6	4	5	1.5	13	easy-running	hardcoat	1	

¹ Acceptance only with minimum quantity

² Minimum yarn distance [mm]



Rieter Components Germany GmbH

Temco
Fuldaer Str. 19
97762 Hammelburg
T +49 9732 87 0
info@temco.de

www.temco.de

The data and illustrations in this brochure and on the corresponding data carrier refer to the date of printing. Temco reserves the right to make any necessary changes at any time and without special notice. Temco systems and Temco innovations are protected by patents.

3507-v2 en 2412